

# **H-80 Series High Flow Humidifier**

Provide more better oxygen therapy with High Flow



## H-80 Series

BMC new H-80 Series high-flow oxygen therapy, highly integrated design, to meet more needs of clinical treatment

- provide a maximum of 80L / min air-oxygen mixed gas, oxygen concentration can be set automatically, providing an exclusive patent AutoFlow function, SmartFlow function.
- Disinfection-free design, Water chamber has a backflow prevention valve to prevent gas backflow, and overall maintenance is more convenient.


#### Can set target oxygen concentration, temperature and flow

- Control target oxygen concentration automatically, oxygen delivery in the machine, 21% -100%, accurate to 1%; Wall oxygen source, oxygen cylinder, oxygen generator can support it; The built-in ultrasonic oxygen sensor requires no maintenance.
- $\bullet$  9-stage humidification temperature: 29  $\degree$  -37  $\degree$  , accurate to 1  $\degree$  .
- Advanced dual fan design, two levels of HFlow and LFlow, 2 L / min ~ 80 L / min, can meet patients of most ages.
- Innovative 7-level humidity compensation function, providing ± 3 adjustable humidity compensation, easily coping with various harsh temperature and humidity environments

#### Innovative High Flow model

AutoFlow<sup>™</sup>


Automatically set the output flow parameters based on the peak expiratory flow(PEF) of the patient, simplifying the setting steps, satisfying the treatment effect and improving patient comfort





#### SmartFlow<sup>®</sup>

Follow the patient's every breath, switch the flow between breaths, provide a higher flow when inhaling, and a lower flow when exhaling, follow your every breath like a bi-level ventilator, comfortable and more economical oxygen resources.







 H-80 Series has a hot standby function, which allows you to continue warm oxygen therapy at any time without turning off the machine for a short time to leave, saving oxygen without having to wait for warm-up time.

### More comprehensive monitoring indexes

 Real-time monitoring of Oxygen Concentration, Flow, Temperature, Respiratory Rate, sPEEP.



#### Simple installation and easy setup

 Integration, disinfection-free design, saving clinical use and maintenance time.

### H-80 Series

H-80 Series High Flow Oxygen Therapy, can be used for patients with spontaneous breathing, including artificial airway respiratory insufficiency, and can be used for patients in hospitals and long-term care institutions.

• In high flow mode, flow rate is 2 L / min ~ 80 L / min, which can set the concentration of inhaled oxygen automatically.

#### Accessories



#### Recommended flow and range for high flow oxygen therapy

The following table lists the recommended starting flows and flow ranges for clinical studies on high flow oxygen therapy

	1	0	15	20	25	30	35	40	45	50	55	60	65	70	75	80	
acute hypoxemic respiratory failure (pneumonia)										•							Macé et al. 2019
extubated patients at high risk of reintubation										•							Hernández et al Oct 2016
extubated patients at low risk of reintubation						•											Hernández et al Apr 2016
acute undifferentiated shortness of breath in the ED										•							Bell et al 2015
acute hypoxemic respiratory failure (pre-intubation)							-			•		_					Frat et al 2015
hypoxemic patients post cardiothoracic surgery						-			•			_					Stéphan et al 2015
post extubation with acute respiratory failure										•							Maggiore et al 2014
do not intubate patient with hypoxemic respiratory distress						-			•			_					Peters et al 2013
acute respiratory failure								-		•		_					Sztrymf et al 2011
mild-to-moderate hypoxemic respiratory failure							•										Parke et al 2011
post-cardiac surgery							•			-							Corley et al 2011
COPD				•													Storgaard et al 2018
COPD						•											Nagata et al. 2018
stable severe COPD patients											_	-•					Cirio et al 2016
COPD and/or bronchiectasis				_													Rea et al 2010

### H-80 Series

	H-80AS	H-80A	H-80M
Adjustment Method of Oxygen Concentration	Auto	Auto	Manual
Flow Monitoring	Monitorable, Adjustable	Monitorable, Adjustable	Monitorable, Adjustable
Flow Rate	2L ~ 80L/min	2L ~ 80L/min	2L ~ 80L/min
Oxygen Concentration Adjustment Range	21% ~ 100%	21% ~ 100%	21% ~ 100%
★Temperature Output Range	<b>29</b> °C ~ <b>37</b> °C	29°C ~ 37°C	29°C ~ 37°C
★Temperature Adjustment Gear	9 steps adjustable	9 steps adjustable	9 steps adjustable
Whether the host is disinfection-free	Yes	Yes	Yes
Screen Size	3.5 inches	3.5 inches	3.5 inches
Trend Review Function	1 day; 3 days; 7 days	1 day; 3 days; 7 days	1 day; 3 days; 7 days
Oxygen Concentration Monitoring	Monitorable, Adjustable	Monitorable, Adjustable	Monitorable
Temperature Monitoring	Monitorable, Adjustable	Monitorable, Adjustable	Monitorable, Adjustable
★sPEEP Monitoring	Monitorable	Monitorable	Monitorable
★Respiratory Rate Monitoring	Monitorable	Monitorable	Monitorable
Automatic filter replacement function	Yes, can be set	Yes, can be set	Yes, can be set
Automatic water refill tips	Yes	Yes	Yes
★ AutoFlow	Yes	1	/
★ SmartFlow	Yes	1	/
Humidity Compensation	-3~+3, 7 steps adjustable	-3~+3, 7 steps adjustable	-3~+3, 7 steps adjustable
★sPEEP	0~4 steps adjustable	1	/
★Hot Standby	Yes	Yes	Yes

BMC Medical Co., Ltd.

Room 110, Tower A Fengyu Building, No.115 Fucheng Road, Haidian, 100036 Beijing, China Tel: +86-10-5166 3880 Fax: +86-10-5166 3880 ext. 810 ST-SC-20-02-02-24-001-Ver1.0 en.bmc-medical.com